HighLevel Custom Fields for Constant Contact

Purpose

HighLevel stores a copy of important Constant Contact metadata.

These fields allow staff and n8n to determine:

- whether the contact exists in Constant Contact,
- the contact's Constant Contact ID,
- subscription status,
- opt-in information,
- opt-out information,
- list membership,
- and synchronization dates.

Custom Field Folder

The Constant Contact fields are grouped under:

```
ConstantContact
```

in HighLevel.

Required Fields

Constant Contact Contact ID

HighLevel Field ID:

```
gm2Ly9W6xLDru1LSlicD
```

HighLevel Field Key:

```
contact.constant_contact_contact_id
```

Purpose:

Stores the permanent Constant Contact contact UUID.

This is the most important integration identifier.

Constant Contact Permission

Field ID:

```
nTrcIwgRVFnb9HGV9iwZ
```

Field Key:

```
contact.constant_contact_permission
```

Purpose:

Stores Constant Contact's current email permission state.

Examples may include:

```
explicit
implicit
unsubscribed
pending_confirmation
temp_hold
not_set
```

Constant Contact Confirm Status

Field ID:

```
a6B5TKDUqJbS8Qakomdq
```

Field Key:

```
contact.constant_contact_confirm_status
```

Purpose:

Stores the Constant Contact confirmation state.

Constant Contact Opt-In Source

Field ID:

```
giaA1ZrkNAzdQeagRsXI
```

Field Key:

```
contact.constant_contact_optin_source
```

Purpose:

Records the source associated with the Constant Contact opt-in.

Constant Contact Opt-In Date

Field ID:

```
pPfeN2PW7cGCvZ2m8Niy
```

Field Key:

```
contact.constant_contact_optin_date
```

Purpose:

Stores the Constant Contact opt-in timestamp.

Constant Contact Opt-Out Source

Field ID:

```
XMLc2K5kXkOqhkmMIFVY
```

Field Key:

```
contact.constant_contact_optout_source
```

Purpose:

Stores the source of an unsubscribe or opt-out event.

Constant Contact Opt-Out Date

Field ID:

```
OrUpspdqU3QJeOkpq0zL
```

Field Key:

```
contact.constant_contact_optout_date
```

Purpose:

Stores the timestamp of the Constant Contact opt-out.

Constant Contact List IDs

Field ID:

```
BAWPByYVSF4dW08fsMzX
```

Field Key:

```
contact.constant_contact_list_ids
```

Purpose:

Stores the Constant Contact list IDs associated with the contact.

Multiple list IDs may be stored as a comma-separated value.

Constant Contact Created At

Field ID:

```
3ze7a09mVWXpwhGFwcMS
```

Field Key:

```
contact.constant_contact_created_at
```

Purpose:

Stores the original Constant Contact creation timestamp.

Constant Contact Updated At

Field ID:

```
QPzcVm3AWqNC2u1OG2Ly
```

Field Key:

```
contact.constant_contact_updated_at
```

Purpose:

Stores the most recent Constant Contact update timestamp known to the integration.

Revision #1
Created 2026-09-22 02:41:54 UTC by David Prata
Updated 2026-09-22 02:44:57 UTC by David Prata